


# Datasheet

## Surge protection of power supply

### SPD type 2 for AC power supplies / EL series



Complete modul NPE lightning current arrester.

- Test standard: IEC 61643-11 / EN 61643-11
- Vibration test standard: DIN EN 60068-2-6, IEC 60068-2-6
- Shock test standard: DIN EN 60068-2-27, IEC 60068-2-27
- Mounting on 35 mm DIN rail (EN 60715)

Technical Data		EL-T2/0+1-NPE
IEC category		Type 2 / class II
Nominal voltage AC	UN	230 V~
Max. continuous operating voltage AC (50/60 Hz)	Uc	260 V~
Nominal discharge current (8/20 µs)	In	20 kA
Max. impulse discharge current (8/20 µs)	Imax	40 kA
Protection level N-PE	Up	≤ 1,5 kV
Follow-on current extinguishing capability AC N-PE	Ifi	100 Aeff
Short-circuit withstand capability at max. back-up fuse	Ik	25 kAeff
Max. acceptable fuse or back-up fuse		125 A gG
Operating temperature range	TU	-40 - +80 °C
Min. conductor cross section at terminals		1.5 mm <sup>2</sup> solid/flexible
Max. conductor cross section		35 mm <sup>2</sup> stranded/25 mm <sup>2</sup> flexible
Enclosure material / colour		Thermoplastic, yellow, UL 97V-0
Degree of protection (IEC EN 60529)		IP 20
Dimension (DIN 43880)		1 TE
Max. connection torque for terminals		3,5 Nm
Composed of: number of modules		1x 38 80 07
Power supply system		between N and NPE

Order Data	
Product	EL-T2/0+1-NPE
Article-No.	38 81 98